



# GLAS-GRIP™ 636 SE

GG-636 SE

## Fast Tacking, Solvent Based Insulation Adhesive

A solvent based, flammable (wet,) self extinguishing (dry) insulation adhesive. GLAS-GRIP 636 SE insulation adhesive offers **exceptional strength**, low viscosity for easy application. GLAS-GRIP's **exceptional coverage and fast tack** means **reduced labor** and overall **lower application costs**.

### TECHNICAL DATA

Color .....	Red (wet) Clear (dry)
Consistency .....	Low viscosity liquid
Base .....	Synthetic polymers & resins
Solvent .....	Aliphatic
Weight per Gallon .....	6.5 lbs.
Solids Content .....	33.0 %
Viscosity .....	200 cps
Coverage .....	500-700 sq.ft. per gallon
Tack Time .....	Immediate
Open Time .....	Approximately 15 minutes
Service Temperature .....	-20°F to 200°F
Water Resistance .....	Excellent
Mildew Resistance .....	Excellent
VOC .....	543 g/l
Packaging .....	1 gal., 5 gal., 50 gal. drum

UNDERWRITERS LABORATORIES, INC.®

**CLASSIFIED**  
ADHESIVE

Surface Burning Characteristics  
294U

\*Applied to inorganic reinforced cement board

FLAME SPREAD ..... 0  
SMOKE DEVELOPED ..... 0

\*Tested as applied in two 3 inch wide strips 8 inches on center at a coverage of 750 sq. ft./gal. Flash point of finished adhesive, closed cup, less than -10°C.

- **FAST TACKING**
- **NON-COBWEBBING**
- **EXCELLENT COVERAGE**
- **ROLLER, BRUSH OR SPRAY**

### APPLICATION

Temperature .....	35°F to 110°F (1.7°C to 44°C)
Method .....	Brush, Roller or Spray: Binks #62 gun; fluid nozzle #63B, air nozzle #66SD-3 (or equal), 60 psi atomizing air, 20 psi fluid pressure.
Preparation .....	Surface must be dirt, oil, moisture, and grease free.
Rate .....	16 ounces per minute
Clean Up .....	UNN-GRIP™ 798-ES or Solvent (Use safe handling practices.)

### STORAGE

Temperature .....	Below 90°F (32°C)
Shelf Life .....	One year (unopened)
Flammability .....	Extremely flammable. Store according to code.

### PRECAUTIONS

**EXTREMELY FLAMMABLE LIQUID AND VAPOR.** Keep away from sparks and open flame. May cause flash fire. Vapors are heavier than air and may travel to a distant ignition source. Contains heptane solvents. Harmful if swallowed or inhaled. May cause eye irritation. Keep out of the reach of children. Review Material Safety Data Sheet for complete safety information prior to use.

**For Industrial Professional Use Only.**

For additional information contact:



Carlisle Coatings & Waterproofing  
Incorporated  
900 Hensley Lane  
Wylie, Texas 75098  
Phone: (800) 527-7092 FAX: (972) 442-0076  
[WWW.HARDCAST.COM](http://WWW.HARDCAST.COM)